



 Vandal Proof



## | FEATURES |



- High Resolution 1/3" Sony Super HAD CCD
- Mechanical IR Filter
- Uniquely Designed Manual Pan/Tilt Function
- Heavy Duty Vandal Resistant With Security Screw
- 24 High Quality IR LED's: Up To 50 ft. In Darkness
- Built-in Auto-Iris & Vari-Focal 4~9mm Lens
- External Zoom & Focus Adjustment

## | SPECIFICATIONS |

Model	CC-9105DHL2
Image Pick-up Device	1/3" Sony Super HAD CCD
Total Pixels	NTSC: 811(H)x508(V), PAL: 795(H)x596(V)
Effective Pixels	NTSC: 768(H)x494(V), PAL: 752(H)x582(V)
Scanning System	Interlace
Frequency	NTSC:15,374KHz(H)/59.94Hz, PAL:15,625KHz(H)/50Hz
Horizontal Resolution	More than 540 TV Lines
Video Output	1Vp-p, 75Ω composite
S/N (Y signal)	50dB (AGC OFF)
Minimum Illumination	0.3Lux/F1.2(Color), 0.1Lux/F1.2(B/W)
Color	Auto Day/Night
Gain Control	Off/Low/Middle/High
White Balance	ATW/AWC/Manual/Fixed
Shutter Speed	Auto/Fixed/Manual/FLK
Backlight	On/Off
Iris Control	Auto, DC Iris
AGC Control	Low/High
Mirror	Built-in (Horizontal Image Inversion)
Lens Mount	Vari-Focal DC Auto Iris Lens 4~9mm
Supplied Voltage	9.5V~15V(12V ± 0.5V Recommended)
Power Supply	DC12V/140mA(Max 1.7W) (CDS ON:450mA Max)
IR Range	50 ft.
LED Quantity	24 pcs.
Operating Temperature	14°F~122°F (-10°C~50°C)
Operating Humidity	10~85% RH
Dimensions	4.72(W) in. x 3.94 in.
Weight	Approximately 1.76 lbs.

\*Specifications Subjected to Change Without Prior Notice.

**AMEBA**  
Since 1995